PRODUCT SPECIFICATIONS

MyWay™ Occasional Tables

May 2015







TECHNICAL SPECIFICATIONS

Model/Family Numbers

* Table Families—MYTB

Base Construction

Table bases are ¾" O.D. 16 gauge round steel tubing, welded to a 12 gauge steel spider. The legs are fastened to the table top with #10 x ¾" long wood screws. The bases are finished in optional chrome. Powder coat paint is available in standard KI paint colors. See Color Addendum.

Table Top Construction

Table tops are .035 thick plastic laminate top surface, glued over 45lb density particle board. A 1/32" phenolic backer is laminated on the underside for balanced laminate construction and helps prevent moisture absorption in the core material. Finished table top width is 1-1/4". The table edge band is KI 2mm PVC (74P) and is available in a variety of colors. Laminate colors are per KI Color Addendum.

Optional AC Power and USB Charger - MyWay Table

The USB/AC power module houses two 125 volt, 15 amp AC outlet and four 5V DC, USB (type 2.0 and type 3.0 compatible) charging plug-in receptacles with 2.1 amp DC total power (no data). The power cord is a 10 ft 14 AWG 15 amp NEMA rated three conductor SJT, with a three prong grounded plug. The circuitry is contained in an extruded aluminum housing. The power cord is strain relief mounted to the rear of the housing. The entire electrical power module assembly is UL listed, having a UL spill test rating for protection against liquids.

All USB ports can power and charge separate iPads, simultaneously.

The Optional Power Module is available in three powder coat colors (Black, White, Silver) and is only available on the 24 x 42 x 16 size table.

Table Glides

Table glides are black, non-marring polypropylene.

1330 Bellevue Street • P.O. Box 8100 • Green Bay, WI 54308-8100 • 1-800-424-2432 • www.ki.com
© 2015 KI All Rights Reserved • Litho in USA • Code KI-62582R3/KI/PDF/0515

Furnishing Knowledge®