CARE & MAINTENANCE

Apply™ Seating

March, 2016



GENERAL CLEANING

Apply seating requires minimal maintenance. It requires no more care than any other fine seating. Proper care and careful use are the best methods of maintaining the appearance, finish, and function of any product.

LAMINATE SHELLS

To clean the laminate, use a mild solution of water and detergent on a soft cloth. (Pine cleaner and warm water works well.) Wipe clean with a dry cloth. Do not soak product. Some stains such as grape juice may be removed by wetting the surface and sprinkling with baking soda, then wiping clean with a damp cloth. (Do not allow the baking soda to remain more than two minutes.) As always, thoroughly dry the surface with a dry cloth. Never use harsh abrasives such as Comet cleanser, scrub pads, etc. to clean the surface. The exposed plywood edge is finished in Tung oil. Avoid contact with solvents. Furniture polish may be applied to maintain a bright attractive finish on the entire laminate shell.

FABRIC UPHOLSTERY

Use a foam-type cleaner such as Johnson Wax "Glory" or Earl Grissmer Co. "Blue Lustre" for general cleaning. For more stubborn spots and stains, use Texie Chemical Co's "K2r". Always follow the manufacturer's directions.

STACK CHAIR FRAMES

It is recommended that frames be kept dry and away from water, rain, ice, snow, and salt.
To clean frames, use warm water and mild soap, then dry thoroughly. Wax or furniture polish may be applied after cleaning.

CAUTION: Do not use a coarse cloth when applying cleaning agents to smooth surfaces.

1330 Bellevue Street • P.O. Box 8100 • Green Bay, WI 54308-8100 • 1-800-424-2432 • www.ki.com
© 2016 Krueger International, Inc. All Rights Reserved • Code KI-62624R1/PDF/0316

Furnishing Knowledge®