
Mesh back sled base 114036

Overall dimensions	23.5″w x 24.25″d x 35.25″h	**Weight**	19 lbs.
Seat dimensions	20″w x 17.75″d x 18.5″h	**Cubic feet**	15
Seat to top of back	1″	**COM**	.75 yds.
Top of arm to floor	26″	**COL**	15 sq. ft.
Top of arm to seat	7.75″		



Standard features	Options available
• Mesh back with upholstered seat • Powder coat base • Fixed arms • All styles rated up to 300 lbs.	• Frame in carbon or chalk • All standard and studio powder coats on base • Eight mesh colors

Mesh back 5 star base 114015

Overall dimensions	26″w x 27″d x 33.5/38″h	**Weight**	21 lbs.
Seat dimensions	20″w x 17.75″d x 16.5/21″h	**Cubic feet**	15
Seat to top of back	18″	**COM**	.75 yds.
Top of arm to floor	24.5″/29″	**COL**	15 sq. ft.
Top of arm to seat	7.75″		



Standard features	Options available
• Mesh back with upholstered seat • Nylon base with caster • Fixed arms • Knocked down • All styles rated up to 300 lbs.	• Frame in carbon or chalk • Carbon or chalk nylon base • Black hard wheel or soft wheel casters • Eight mesh colors • Fully assembled

Mesh back 4 star base 114115

Overall dimensions	23.5″w x 23.75″d x 35.5″h	**Weight**	21 lbs.
Seat dimensions	20″w x 17.75″d x 18″h	**Cubic feet**	15
Seat to top of back	18″	**COM**	.75 yds.
Top of arm to floor	25.75″	**COL**	15 sq. ft.
Top of arm to seat	7.75″		



Standard features	Options available
• Mesh back with upholstered seat • Powder coat base • Fixed arms • All styles rated up to 300 lbs.	• Frame in carbon or chalk • All standard and studio powder coats on base • Glides, black hard wheel or soft wheel casters • Eight mesh colors

Standard textile selection

https://ofs.com/resources/textiles

Frame construction

Shell	• Injection-molded, glass-reinforced nylon resin
Upholstery	• Mesh: constructed of 40% elastomer, 60% polyester • All mesh colors conform to CAL Tech Bulletin 117-2013
Arms	• Integrated fixed loop arms
Seat Foam	• Molded foam with a density of 3 pounds per cubic foot • CAL TB 117-2013 compliant
Control	• 114015 only: Swivel tilt with 1 position lock
Base	• 5 star Injection molded, glass reinforced nylon resin on model 114015 • 4 star cast aluminum on model 114115 • Cantilever steel tube base on model 114036
Cylinder	• Class 4 gas cylinder provides height adjustment of 4.5” on model 114015 • Swivel post without height adjustment on model 114115
Casters	• Twin wheel casters manufactured of injection molded nylon resin • 60mm diameter hoodless design
Assembly	• Self locking, hardened steel, hex/Phillips head bolts